



SENSING INNOVATION

Top notch **Sensor Solutions** by Sensinova

www.sensinova.in







NANO 16

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-12min Load Capacity: 6Amp

Detection Distance: 2-16m (Radius) Adj

IP Ratina: IP20



NOVA 4T

(Wall / Ceiling Mounted - 180°/360° Detection)

Hold Time: 10sec-12min Load Capacity: 5Amp

Detection Distance: Wall:5-15m Adi.

Ceiling:1-8m (Radius) Adj

IP20 IP Ratina:



NOVA MINI

(Wall/Ceiling Mounted - 180°/360° Detection)

Hold Time: 5sec-30min Load Capacity: 200W LFD Detection Distance: 5-12m (Radius) Adj

IP Ratina: IP20

Manual Override / Bypass



NANO F16

(Flush Mounted - 360° Detection)

Hold Time: 10sec-12min Load Capacity:

Detection Distance: 1-8m (Radius) Adj

IP Rating: IP20



NANO W12

(Wall Mounted - 180° Detection)

Hold Time: 10sec-12min Load Capacity: 5Amp

Detection Distance: 5-12m (Adjustable)

IP65 IP Ratina:



NANO HB20

(Highbay Sensor - 360° Detection with 1-10v Dimming)

Hold Time: 5sec-30min Load Capacity: 5Amp

Detection Distance: 4-10m (Radius) Adi

IP Rating: IP65



NOVA DC NONC

(Ceiling Mounted - 360° Detection)

Input: 12-24V / DC Hold Time: 8sec-12min Load Capacity: 5Amp Detection Distance: 2-8m (Adjustable)

Dry Contact Output

IP20 IP Ratina:

NOVA PFC-S

(Ceiling Mounted - 360° Detection)

Input: 220-240V / AC Hold Time: 8sec-12min Load Capacity: 7Amp (Dry Contact) Detection Distance: 8m Max (Adjustable)

IP Rating: IP20

Dry Contact Output





IRIS S8

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-7min Load Capacity: 200W LED Detection Distance: 8m Max (<24°C)

IP Rating: IP20



IRIS F8

(Flush Mounted - 360° Detection) Hold Time: 10sec-12min Load Capacity: 200W LED

Detection Distance: 8m Max (<24°C)

IP Rating: IP20



IRIS S12

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-7min Load Capacity: 5Amp

Detection Distance: 12m Max (<24°C)

IP Rating: IP20



IRIS S12W

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-12min Load Capacity: 5Amp

Detection Distance: 8m Max (<24°C)

IP Rating: IP20



IRIS S20 (Occupancy)

(Ceiling Mounted - 360° Detection)

10sec-30min Hold Time:

Load Capacity: 10Amp Detection Distance: 20m Max (<24°C)

IP Rating: IP20



IRIS F20R (Occupancy)

(Ceiling Mounted - 360° Detection)

10sec-30min Hold Time:

10Amp Load Capacity:

Detection Distance: 20m Max (<24°C)

IP Rating: IP20



IRIS S6DR

(Ceiling Mounted - 360° Detection)

Hold Time: 10sec-30min 10Amp Load Capacity: Detection Distance: 6m Max (<24°C)

IP20 IP Rating:



IRIS W15

(Wall Mounted - 180° Detection)

Hold Time: 10sec-12min 5Amp Load Capacity:

Detection Distance: 12m Max (<24°C)

IP Rating: IP65



NEO-E15

(Dual Mode on/off & Waving DC - 12V)

12-24V / DC Input: Output: 5Amp Sensing Distance: 6 to 10cm



NEO-D15

(Dual Mode on/off & Waving DC - 12V)

12-24V / DC Input: 5Amp Output: Sensing Distance: 6 to 10cm



SN-PR123

(Single Door - 230V AC)

220-240V / AC Input: Output: 5Amp Sensing Distance: 6 to 10cm



SN-PC302

220-240V / AC Power Source:

Rated Current: 10A

IP Rating: IP44

LUX Setting: <5-50 Lux (Adjustable)



GET IN TOUCH

- **(%)** +91 95867 74775
- (D) +91 99797 64665
- (1) Sensinova India, C K Patel Estate, Survey Number 372, Opp. Tata Motors Service Centre, Near RamaKaka Deri, Chhani, Vadodara-391740

Scan For More Details



Follow us on:







