

TECHNICAL DATA SHEET



12W TULIP PLUS (2 IN 1) SURFACE MOUNT

TECHNICAL SPECIFICATION

| | |
|--|--|
| Fitting Type | Surface Mount |
| Operating Voltage and Frequency | 175-275V/ 50 Hz |
| Nominal Operating Voltage, Current and Frequency | 230V, 79.5mA @FULL, 230V 17.7mA @DIM 50Hz |
| Input Wattage Rating | 12W@FULL / 2.4W@DIM |
| Functions | LED light will be at its full brightness when there is motion detected and will dim down automatically to 20% after 30 Seconds of no motion detection. |
| Microwave Sensor Range | 4-6 Meter (Radius) |
| Lumens | 1200 |
| Housing Dimensions | Square: 144 x 144mm Round: 144mm ∅ |
| Housing and diffuser type | Polycarbonate |
| LED efficacy | 150 lm/W |
| CCT | 6500K, 4000K |
| Lifespan | 35000 Hours |
| IP Grade | IP 20 |
| Warranty | 1 Year |

DRIVER SPECIFICATION

| | |
|------------------------|---|
| Surge Protection | Up to 4kV |
| Efficiency | >90% |
| Power Factor | <0.98 |
| Functions | ON/OFF - Light will be ON if there is motion and automatically will be OFF when there is no motion detection for 30 Sec. DIM - Light will be at its full brightness if there is motion and automatically the brightness will be reduced to 20% when there is no motion detection for 30 Sec. |
| Microwave Sensor Range | 4-6 Meter (Radius) |

